

MSD-K Series

How to order

● No switch (without magnet for switch)

MSD-K - 6 - 5 - R

● With switch (built-in magnet for switch)

MSD-KL - 6 - 5 - F0H - R - R

A Model No.

B Bore size

C Stroke

D Switch model No.

*1

*2

E Switch quantity

F Option

*3

⚠ Note on model No. selection

*1 : For ø6 or ø8 with switch, use a non-magnetic (stainless steel, etc.) mounting bolt.*2 : For ø12 or ø16 with proximity switch, use a non-magnetic

[Example of model No.]

MSD-KL-6-5-F0H-R-R

A Model No. : Double acting/high load/with switch
B Bore size : ø6 mm
C Stroke : 5 mm
D Switch model No. : Reed F0H switch
E Switch quantity : 1 on rod side
F Option : Rear piping

How to order switch

SW - F0H

Switch model No.
(Item **D** above)

Code		Description					
A Model No.							
MSD-K	Double acting/high load	No switch					
MSD-KL		With switch					
B Bore size (mm)							
6	ø6						
8	ø8						
12	ø12						
16	ø16						
C Stroke (mm)							
5	5						
10	10						
15	15						
20	20						
25	25						
30	30						
D Switch model No.							
Axial lead wire	Radial lead wire	Contact	Voltage		Indicator	Lead wire	
			AC	DC			
F0H*	F0V*	Reed		●	1-color LED	2-wire	
-	F2S*	Proximity		●		3-wire	
F2H*	F2V*			●			
-	F3S*			●			
F3H*	F3V*			●			
F3PH*	F3PV*			●	1-color LED (PNP output) (made to order)	3-wire	
F2YH*	F2YV*			●	2-color LED	2-wire	
F3YH*	F3YV*			●		3-wire	
* Lead wire length							
Blank			1 m (standard)				
3			3 m (option)				
E Switch quantity							
R	1 on rod side						
H	1 on head side						
D	2						
F Option							
Blank		Front piping					
R		Rear piping					

Specifications for rechargeable battery

(Catalog No. CC-1226A)

● Design compatible with rechargeable battery manufacturing process

MSD-K - - P4*