

SSD2-G Series

How to order

No switch (without magnet for switch)

SSD2-G - **32** - **5** - **N** - **LB** - **I**

With switch (built-in magnet for switch)

SSD2-GL - **32** - **10** - **T0H** - **R** - **N** - **LB** - **I**

A Model No.

B Bore size

C Stroke

D Switch model No.

*1

*2

*5

*6

E Switch quantity

F Option

G Mounting bracket
*3
*8

⚠ Precautions for model No. selection

- *1 : The T8* switch cannot be mounted on the ø20 to ø32 bore sizes.
- *2 : The F-switch can only be mounted on the piping port surface of bore sizes ø20 and ø25.
- *3 : The mounting bracket is included at shipment.
- *4 : "I" and "Y" cannot be selected together.
- *5 : The F-switch with L type lead wire on ø20 models cannot be selected on strokes of 15 mm or under.
- *6 : Switches are shipped with the product. Contact CKD if assembling before shipment is necessary.
- *7 : F-switch cannot be selected.
- *8 : The structure of bore sizes ø20 to ø32 does not permit retrofitting of the foot bracket (LB) or flange bracket (FA) on the rod side. Assembly before shipment is available as made to order.

[Example of model No.]

SSD2-GL-20-10-T0H-R-N-LB-I

Model: Compact cylinder rubber scraper

B Bore size : ø20 mm

C Stroke : 10 mm

D Switch model No.: Reed T0H switch/
Lead wire length 1 m

E Switch quantity : 1 on rod side

F Option : Rod end male thread

G Mounting bracket: Axial foot

H Accessory : Rod eye

H Accessory
*4

Code		Description													
A Model No.															
SSD2-G		Double acting/single rod/rubber scraper													
SSD2-GL		Double acting/single rod/rubber scraper/with switch													
B Bore size (mm)															
20		ø20													
25		ø25													
32		ø32													
40		ø40													
50		ø50													
63		ø63													
80		ø80													
100		ø100													
C Stroke (mm)															
Refer to the stroke table on the following page.															
D Switch model No.															
Lead wire	Lead wire	Contact	Voltage		Indicator	Lead	Bore size								
Straight	L-shaped		AC	DC		wire	20	25	32	40	50	63	80	100	
-	F2S*	Proximity		●	1-color LED	2-wire	●	●							
-	F3S*			●		3-wire	●	●							
F2H*	F2V*			●		2-wire	●	●							
F3H*	F3V*			●		3-wire	●	●							
F3PH*	F3PV*			●	1-color LED (PNP output) (custom)	3-wire	●	●							
F2YH*	F2YV*			●	2-color LED	2-wire	●	●							
F3YH*	F3YV*		●	3-wire		●	●								
T0H*	T0V*	Reed	●	●	1-color LED	2-wire	●	●	●	●	●	●	●	●	
T5H*	T5V*		●	●	No indicator lamp		●	●	●	●	●	●	●	●	
T8H*	T8V*		●	●	1-color LED					●	●	●	●	●	
T1H*	T1V*	Proximity	●		1-color LED	2-wire	●	●	●	●	●	●	●	●	
T2H*	T2V*			●			●	●	●	●	●	●	●	●	
T3H*	T3V*			●		1-color LED (PNP output)	3-wire	●	●	●	●	●	●	●	●
T3PH*	T3PV*			●				●	●	●	●	●	●	●	●
T2WH*	T2WV*			●	2-color LED		2-wire	●	●	●	●	●	●	●	●
T2YH*	T2YV*			●		●		●	●	●	●	●	●	●	
T3WH*	T3WV*			●		2-color LED	3-wire	●	●	●	●	●	●	●	●
T3YH*	T3YV*			●				●	●	●	●	●	●	●	●
T2YD*	-				2-color LED		2-wire	●	●	●	●	●	●	●	●
T2YDT*	-			●	AC magnetic field	●		●	●	●	●	●	●	●	
T2JH*	T2JV*			●	1-color LED off-delay	2-wire	●	●	●	●	●	●	●	●	
* Lead wire length															
Blank		1 m (standard)													
3		3 m (option)													
5		5 m (option)													
E Switch quantity															
R		1 on rod side													
H		1 on head side													
D		2													
F Option															
Blank		Rod end female thread													
N		Rod end male thread													
G Mounting bracket															
Blank		Without mounting bracket													
LB		Axial foot (made-to-order product)													
CB		Clevis bracket (pin and snap ring included)													
FA		Rod side flange (made-to-order product)													
FB		Head side flange													
H Accessory (available when rod end male thread “N” is selected)															
I		Rod eye													
Y		Rod clevis (pin and snap ring included)													

[Stroke table]


Stroke (mm)		Applicable bore size							
		20	25	32	40	50	63	80	100
Standard stroke	5	●	●	●	●				
	10	●	●	●	●	●	●	●	●
	15	●	●	●	●	●	●	●	●
	20	●	●	●	●	●	●	●	●
	25	●	●	●	●	●	●	●	●
	30	●	●	●	●	●	●	●	●
	35	●	●	●	●	●	●	●	●
	40	●	●	●	●	●	●	●	●
	45	●	●	●	●	●	●	●	●
	50	●	●	●	●	●	●	●	●
	75			●	●	●	●	●	●
	100			●	●	●	●	●	●
Min. stroke (mm) *1		1							
Max. stroke (mm)		50		100					
Custom stroke *2		In 1 mm increments							

1: Less than 5 mm for 1-color LED switch and less than 10 mm for the 2-color LED, off-delay, AC magnetic field proof, T1 or T8* switch are not available.

Refer to page 936 for the min. stroke with switch.

*2: The total length when using a custom stroke is the same as that when using the next longer standard stroke.

How to order switch



How to order mounting bracket

Bore size (mm)	ø20	ø25	ø32	ø40	ø50	ø63	ø80
Mounting bracket							
Foot (LB)				SSD2-LB-40	SSD2-LB-50	SSD2-LB-63	SSD2-LB-80
Flange (FA/FB)				SSD2-FA-40	SSD2-FA-50	SSD2-FA-63	SSD2-FA-80
Clevis bracket (CB)	SSD2-CB-20	SSD2-CB-25	SSD2-CB-32	SSD2-CB-40	SSD2-CB-50	SSD2-CB-63	SSD2-CB-80
Bore size (mm)	ø100						
Mounting bracket							
Foot (LB)	SSD2-LB-100						
Flange (FA/FB)	SSD2-FA-100						
Clevis bracket (CB)	SSD2-CB-100						

*1: The foot mounting bracket is provided as 2 pcs./set.

*2: The structure of bore sizes ø20 to ø32 does not permit retrofitting of the foot bracket (LB) or flange bracket (FA) on the rod side. Contact CKD for details.

SCP*3

CMK2

CMA2

SCM

SCG

SCA2

SCS2

CKV2

CAV2/
COVP/N2

SSD2

SSG

SSD

CAT

MDC2

MVC

SMG

MSD/
MSDG

FC*

STK

SRL3

SRG3

SRM3

SRT3

MRL2

MRG2

SM-25

ShkAbs

FJ

FK

Spd
Contr

Ending